



Induction Live Cook Top

Model: LC Induction Live Counter(TT)
 Working Voltage: 220V-50HZ
 Power Input: 2.5 kW ; 8540 Btu
 Rated current input(A): 11.5
 Working Temp range(°C): -10°C~45°C
 Min Temp(°C): 55°C
 Max Temp(°C): 300°C
 Efficiency : 90%
 Noise level: 50db
 Max payload Kgs: 15
 Body : S.S., Toughened Heat Treated Glass Top
 Machine size(mm):L×W×H:350x350x125
 Net Weight(Kgs): 08



Induction For Bulk Cooking 5kwh

Model: 5kWh Induction Stove(SA)
 Working Voltage: 220V-50HZ
 Power Input: kW-5 ; Btu-17080
 Rated current input(A): 23
 Working Temp range(°C): -10°C~45°C
 Min Temp(°C): 55°C
 Max Temp(°C): 300°C
 Efficiency : 90%
 Noise level: 150db
 Max payload Kgs: 50
 Body : SS Body, Ceramic Top
 Machine size(mm):L×W×H: 450x450x850
 Net Weight(Kgs): 25



Induction Buffet Warmer

Model: BW Induction Buffet warmer(TT)
 Working Voltage: 220V-50HZ
 Power Input: 1.2 kW ; 4100 Btu
 Rated current input(A): 5.5
 Working Temp range(°C): -10°C~45°C
 Min Temp(°C): 55°C
 Max Temp(°C): 180°C
 Efficiency : 90%
 Noise level: 50db
 Max payload Kgs: 25
 Body : S.S., Toughened Heat Treated Glass Top
 Machine size(mm):L×W×H :300x300x100,
 Top Glass 350x350x6
 Net Weight(Kgs): 08



Induction For Bulk Cooking 9kwh

Model: 9kWh Induction Stove(SA)
 Working Voltage: 440V-50HZ
 Power Input: 9kW ; 30744 Btu
 Rated current input(A): 41.4
 Working Temp range(°C): -10°C~45°C
 Min Temp(°C): 55°C
 Max Temp(°C): 300°C
 Efficiency : 90%
 Noise level: 150db
 Max payload Kgs: 80
 Body : SS Body, Ceramic Top
 Machine size(mm):L×W×H :600x600x450
 Net Weight(Kgs): 40



Induction Buffet Warmer

Model: BW Induction Buffet warmer(TT)
 Working Voltage: 220V-50HZ
 Power Input: 1.2 kW ; 4100 Btu
 Rated current input(A): 5.5
 Working Temp range(°C): -10°C~45°C
 Min Temp(°C): 55°C
 Max Temp(°C): 180°C
 Efficiency : 90%
 Noise level: 50db
 Max payload Kgs: 25
 Body : S.S., Toughened Heat Treated Glass Top
 Machine size(mm):L×W×H :300x300x100,
 Top Glass 350x350x6
 Net Weight(Kgs): 08



Induction Live Counter 4 Zone

Model:4x1.8kWh (Four Zone) Stand Alone
 Working Voltage: 220V-50HZ
 Power Input:1.8 x 4 kW ; 6150 x 4 Btu
 Rated current input(A): 8.3 x 4
 Working Temp range(°C): -10°C~45°C
 Min Temp(°C): 55°C
 Max Temp(°C): 300°C
 Efficiency : 90%
 Noise level: 150db
 Max payload Kgs: 18 x 4
 Body : SS Body ,Toughened Heat Treated Glass Top
 Machine size(mm):L×W×H : 600x600x850
 Net Weight(Kgs): 52



Induction Tawa/ Roti Puffer 15 X 27

Model: RP Induction Roti Puffer (SA)
 Working Voltage: 220V-50HZ
 Power Input: 4 kW ; 13664 Btu
 Rated current input(A): 18.4
 Working Temp range(°C): -10°C~45°C
 Min Temp(°C): 55°C
 Max Temp(°C): 380°C
 Efficiency : 90%
 Noise level: 50db
 Max payload Kgs: 25
 Body : SS Body, M.S.Plate 15mm Top
 Machine size(mm):L×W×H : 375x375x850
 Net Weight(Kgs): 45



Induction Live Counter 3 Zone

Model:4x1.8kWh (Four Zone) Stand Alone
 Working Voltage: 220V-50HZ
 Power Input:1.8 x 3 kW ; 6150 x 3 Btu
 Rated current input(A): 8.3 x 3
 Working Temp range(°C): -10°C~45°C
 Min Temp(°C): 55°C
 Max Temp(°C): 300°C
 Efficiency : 90%
 Noise level: 150db
 Max payload Kgs: 12 x 3
 Body : SS,Toughened Heat Treated Glass Top
 Machine size(mm):L×W×H :
 Net Weight(Kgs):



Induction Tawa 22 X 42

Model: 8kWh Induction Tawa 2 Zone 22x42inch (SA)
 Working Voltage: 220V-50HZ
 Power Input: 4 x 2 kW ; 13664 Btu
 Rated current input(A): 18.4 x 2
 Working Temp range(°C): -10°C~45°C
 Min Temp(°C): 55°C
 Max Temp(°C): 300°C
 Efficiency : 90%
 Noise level: 150db
 Max payload Kgs: 60
 Body : SS Body, M.S. PLATE
 Machine size(mm):L×W×H: 1050x550x850
 Net Weight(Kgs): 125



Induction Wok

**Induction Cooking Is
 Faster, Safer, And Cheaper
 Let Us Join The
 4TH GENERATION Eco Friendly
 Method of Cooking.**

WHAT NEEDS TO BE HEATED IS THE FOOD NOT THE CHEF!